

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), amended by
Regulation (EU) 2020/878

VIKTOR
LACQUERS

PRIMER VIKTOR 842

Creation date 23rd January 2026 Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture PRIMER VIKTOR 842
UFI mixture NOAR-Y0W9-D00H-60K2
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
Priming and barrier lacquer for aluminum foil.
Intended for professional/industrial use.
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**
Manufacturer
Name or trade name Viktor Lacquers s.r.o.
Address U Jatek 1551, Nové Město na Moravě, 59231
Czech Republic
Identification number (CRN) 09344781
VAT number CZ09344781
Phone +420 566 618 550
Email info@viktorlac.com
Web address www.viktorlac.com
- Competent person responsible for the safety data sheet**
Name Viktor Lacquers s.r.o.
Email info@viktorlac.com
- 1.4. Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.
- Flam. Liq. 2, H225
Eye Dam. 1, H318
STOT SE 3, H336
Aquatic Chronic 3, H412
- Most serious adverse physico-chemical effects**
Highly flammable liquid and vapour.
- Most serious adverse effects on human health and the environment**
Causes serious eye damage. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

butanone
butan-1-ol

Hazard statements

H225 Highly flammable liquid and vapour.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), amended by
Regulation (EU) 2020/878



PRIMER VIKTOR 842

Creation date 23rd January 2026 Version 2.0

H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/eye protection/protective clothing/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a doctor.
P405	Store locked up.
P501	Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 606-002-00-3 CAS: 78-93-3 EC: 201-159-0	butanone	60-80	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	2, 3
CAS: 68002-26-6 EC: 614-206-9	BENZOGUANAMINE FORMALDEHYDE RESIN, BUTYLATED	5-8	Aquatic Chronic 2, H411	
Index: 603-004-00-6 CAS: 71-36-3 EC: 200-751-6	butan-1-ol	0-3	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336	
Index: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7	xylene	0-0.5	Flam. Liq. 3, H226 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315	1, 2

Notes

- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- A substance for which exposure limits are set.
- Drug precursor

Full text of all classifications and hazard statements is given in the section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), amended by
Regulation (EU) 2020/878



PRIMER VIKTOR 842

Creation date 23rd January 2026 Version 2.0

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

Rinse out the mouth with clean water. In the event of issues, find medical help.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Inhaling vapours can cause corrosion of the breathing system. May cause drowsiness or dizziness.

If on skin

Not expected.

If in eyes

Causes serious eye damage.

If swallowed

Corrosion of the digestion system can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), amended by
Regulation (EU) 2020/878



PRIMER VIKTOR 842

Creation date 23rd January 2026 Version 2.0

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value
butanone (CAS: 78-93-3)	OEL 8 hours	600 mg/m ³
	OEL 8 hours	200 ppm
	OEL 15 minutes	900 mg/m ³
	OEL 15 minutes	300 ppm

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value
xylene (CAS: 1330-20-7)	OEL 8 hours	221 mg/m ³
	OEL 8 hours	50 ppm
	OEL 15 minutes	442 mg/m ³
	OEL 15 minutes	100 ppm

Notes

Skin.

DNEL

butanone			
Workers / consumers	Route of exposure	Value	Effect
Workers	Dermal	1161 mg/kg	Chronic effects systemic
Workers	Inhalation	600 mg/m ³	Chronic effects systemic
Consumers	Dermal	412 mg/kg	Chronic effects systemic

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), amended by
Regulation (EU) 2020/878



PRIMER VIKTOR 842

Creation date 23rd January 2026 Version 2.0

butanone			
Workers / consumers	Route of exposure	Value	Effect
Consumers	Inhalation	106 mg/m ³	Chronic effects systemic

PNEC

butanone	
Route of exposure	Value
Fresh water	55.8 mg/l
Marine water	55.8 mg/l
Freshwater sediment	284.74 mg/kg
Sea sediments	287.7 mg/kg
Soil (agricultural)	22.5 mg/kg

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. When selecting gloves, consider the properties of the product and the duration of exposure. Replace gloves at the first signs of wear or damage. Other protection: Protective antistatic clothing made of natural fibres (cotton) or synthetic fibres resistant to elevated temperatures. Antistatic footwear. Contaminated skin should be washed thoroughly.

Glove material	Thickness	Breakthrough time	Class
Butyl rubber (IIR)	≥ 0.3 mm	>480 min	6

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	data not available
Odour	after solvents
Melting point/freezing point	<-40 °C
butanone (CAS: 78-93-3)	-86 °C
Boiling point or initial boiling point and boiling range	80 °C
butanone (CAS: 78-93-3)	79.6 °C
Flammability	data not available
butanone (CAS: 78-93-3)	inflammable
Lower and upper explosion limit	data not available
butanone (CAS: 78-93-3)	1.8 % 11.5 %
Flash point	-6 °C
butanone (CAS: 78-93-3)	-9 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), amended by
Regulation (EU) 2020/878



PRIMER VIKTOR 842

Creation date 23rd January 2026 Version 2.0

Auto-ignition temperature	data not available
butanone (CAS: 78-93-3)	404 °C
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	data not available
Solubility in water	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
butanone (CAS: 78-93-3)	126 hPa at 25 °C 105 hPa at 20 °C
Density and/or relative density	
Density	0.93 g/cm ³
butanone (CAS: 78-93-3)	0.805 g/cm ³
Relative vapour density	data not available
Particle characteristics	data not available

9.2. Other information

Content of organic solvents (VOC) 595 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No risks of reactions with other substances are known under normal conditions.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Hazardous substances in concentrations exceeding exposure limits may cause acute inhalation poisoning, depending on the concentration and duration of exposure. No toxicological data is available for the mixture.

Acute toxicity

Based on the available data, the criteria for classification of the mixture are not met.

PRIMER VIKTOR 842						
Route of exposure	Parameter	Value	Exposure time	Species	Sex	Value determination
Oral	ATE	16667 mg/kg				Calculation of value
Dermal	ATE	220000 mg/kg				Calculation of value
Inhalation (vapor)	ATE	2200 mg/l				Calculation of value

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), amended by
Regulation (EU) 2020/878



PRIMER VIKTOR 842

Creation date 23rd January 2026 Version 2.0

butanone						
Route of exposure	Parameter	Value	Exposure time	Species	Sex	Value determination
Oral	LD ₅₀	>2000 mg/kg		Rat (Rattus norvegicus)		
Dermal	LD ₅₀	>2000 mg/kg		Rabbit		
Inhalation	LC ₅₀	>5000 ppm				

Skin corrosion/irritation

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

Irritation

butanone			
Route of exposure	Result	Exposure time	Species
Skin	Moderate irritant		Rabbit
Eye	Highly irritating		Rabbit

Serious eye damage/irritation

Causes serious eye damage. Data for the components of the mixture are not available.

Respiratory or skin sensitisation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness. Data for the components of the mixture are not available.

Toxicity for specific target organ - repeated exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), amended by
Regulation (EU) 2020/878



PRIMER VIKTOR 842

Creation date 23rd January 2026 Version 2.0

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Acute toxicity

butanone				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	>100 mg/l	48 hours	Fish (Leuciscus idus)	
EC ₅₀	>100 mg/l	48 hours	Invertebrates (Daphnia magna)	
EC ₅₀	>100 mg/l	72 days	Algae (Scenedesmus subspicatus)	

12.2. Persistence and degradability

No data are available for either the mixture or the components.

12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

Packaging waste type code

15 01 10* packaging containing residues of or contaminated by hazardous substances

15 02 02* absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by hazardous substances

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

UN 1993

14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (Butan-2-one)

14.3. Transport hazard class(es)

3 Flammable liquids

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), amended by
Regulation (EU) 2020/878



PRIMER VIKTOR 842

Creation date 23rd January 2026 Version 2.0

14.4. Packing group

II

14.5. Environmental hazards

No

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

Not known

Additional information

Hazard identification No.

33

UN number

1993

Classification code

F1

Safety signs

3



Tunnel restriction code

(D/E)

Air transport - ICAO/IATA

Packaging instructions passenger

355

Cargo packaging instructions

366

Marine transport - IMDG

EmS (emergency plan)

F-E, S-E

MFAG

310

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), amended by
Regulation (EU) 2020/878



PRIMER VIKTOR 842

Creation date 23rd January 2026 Version 2.0

Guidelines for safe handling used in the safety data sheet

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/eye protection/protective clothing/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a doctor.
P405	Store locked up.
P501	Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox.	Acute toxicity
ADR	Agreement concerning the international carriage of dangerous goods by road
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
ATE	Acute toxicity estimate
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50 % of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency Response Procedures for Ships Carrying Dangerous Goods
EU	European Union
EuPCS	European Product Categorisation System
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
log Kow	Octanol-water partition coefficient
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulation concerning the International Carriage of Dangerous Goods by Rail
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure
UN number	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), amended by
Regulation (EU) 2020/878



PRIMER VIKTOR 842

Creation date	23rd January 2026	Version	2.0
---------------	-------------------	---------	-----

VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.
